

with exclusive vibroslant action for complete, thorough blending of popular heavily pigmented acrylic enamels and lacquers.

EXPLOSION PROOF
... FIREPROOF

non-electric

 AVOIDS COLOR MISMATCHING caused by pigments settling in a matter of minutes unless paint is mixed just before using.

MIXES 1-GALLON in 4 to 6 minutes . . .
 PINTS and QUARTS even faster.

 OPERATES ANYWHERE on 35 to 80 psi compressed air (50 to 60 lbs. recommended.)

HEAVY-DUTY SAFE...FAST

**MODEL 3100** 

PATENTED

# A MUST FOR AUTO BODY SHOPS

Major automobile and paint manufacturers recommend that dealers equip their shops with a Paint Shaker for truer mixing and matching of colors. Performance of Hinson PAINT SHAKER confirmed by laboratory testing by leading maker of automotive refinishing products. (Proof available.)

Height 9"

Length 17"

Width 10"

Shipping weight approximately 17 lbs.

SHIPPED COMPLETELY ASSEMBLED READY TO HOOK UP TO SNAP-ON COUPLING ON YOUR AIR COMPRESSOR LINE.



### COMPLETE, THOROUGH BLENDING AT 500 SHAKES A MINUTE

Whether it's a 1-gallon or a smaller can of paint, the Hinson PAINT SHAKER quickly mixes and blends the color into desired brushing or spraying consistency. Just insert the can into the "basket" . . . tighten the disc firmly against the top of the can . . . turn on the compressed air. PAINT SHAKER does the rest.

# SO SAFE YOU CAN STOP AND START IT BY HAND

Even when vibrating at top speed, PAINT SHAKER can be stopped safely by pressing a hand against the side of the "basket." A slight nudge restarts the vibrating action.

# QUIET OPERATION

No loose parts, no motor, no reduction gears to produce noise and rattle.

#### LIGHTWEIGHT FOR PORTABILITY

Entire unit can be carried easily . . . moved from one job site to another.

#### RUGGEDLY BUILT FOR HEAVY DUTY

Precision die cast base; solidly welded heavy strap steel "basket." Base finished in long-lasting baked blue enamel; "basket" in white baked enamel.





#### EASILY INSTALLED ANYWHERE

Bolts to counter surface or workbench. If PAINT SHAKER is likely to be moved from place to place, a metal bar may be bolted to front legs to permit SHAKER to be secured with "C" clamps to a workbench. "C" clamp attachment also permits SHAKER to be attached to a pick-up truck for delivering pre-mixed paint to separate job sites.

#### YEARS OF SERVICE-FREE OPERATION ASSURED BY FEWER WEAR PARTS

Test models have operated continuously for more than 800 hours without servicing. The few wearable parts can be replaced if need be in any shop. No need to return SHAKER to factory for service.

#### WARRANTY

Hinson Manufacturing Company guarantees every PAINT SHAKER for 90 days against defects in workmanship or materials. Hinson will replace defective parts without charge if Warranty Card is on file at the factory.



